

INWALLKIT

In-Wall Power Filter and Connection Kit for wall or ceiling-mounted displays.



Power conditioners like the APC AV S Type do an excellent job in protecting connected equipment from surges, fluctuating voltage, excessive electrical interference and even complete loss of power. Installers have been challenged with protecting remote devices from the power anomalies that affect the rest of the system. Until now.

The INWALLKIT is a code-compliant device, designed to deliver the same level of protection to wall or ceiling-mounted displays. The all metal construction shields against radiated EMI and the built-in filter circuit mitigates interference induced on the line between the Power Conditioner and the INWALLKIT.

The "Filtering" LED signals the unit is functioning properly and the "Wiring OK" LED lets the installer know the wiring is correctly installed. The INWALLKIT comes in black or white to match most contemporary home décor.

Product Benefits

- Protection from the Power Conditioner is delivered to the remotely located display
- Additional filtering guards against radiated EMI interference
- Fully compliant with National Electric Code
- Equipment Protection Policy from the connected APC Power Conditioner is transferred to the remote display
- Lifetime Warranty ensures peace of mind

Protection

Isolated filter banks Eliminates electromagnetic and radio frequency interference (EMI/RFI) as a source of audio-video signal degradation.

Safety-agency approved Ensures the product has been tested and approved to work safely with connected equipment and within the specified environment. UL, FCC approvals.

Manageability

LED status indicators Quickly understand unit and power status with visual indicators

Features and Specifications



Models	Model Number	Model Number
	INWALLKIT-BLK	INWALLKIT-WHT
Color	Black	White
INPUT		
Nominal Voltage	120 Vac	120 Vac
Rated Input Current	15 Amps	15 Amps
Input Circuit Breaker Rating	15A	15A
OUTPUT		
Number of Outlets (all outlets are surge protected and filtered for EMI/RFI)	2	2
Outlet Type	NEMA 5-15R (tested to UL498)	NEMA 5-15R (tested to UL498)
Rated Output Capacity	15A	15A
PHYSICAL		
Unit Dimensions	9.5" x 17.1" x 1.7"	9.5" x 17.1" x 1.7"
Unit Weight	8.6 lbs	8.6 lbs
CONFORMANCE		
Safety Agency Approvals	cETLus per UL1283 and UL514D	cETLus per UL1283 and UL514D
WARRANTY		
Lifetime Equipment Protection Policy (see policy for details)	Relevant Power Conditioner EPP Prevails	Relevant Power Conditioner EPP Prevails
Product Warranty	Lifetime	Lifetime

