QX3CS pr. QX SERIES IN-WALL 3" 2-WAY SHALLOW DEPTH IN-WALL DUAL MONAURAL CENTERGY PAIR







Size Custom h x 7.27 w x 3.875 d (in) 678 h x 184 w x 89 d (mm) Freq Response 70Hz-24kHz±3dB Impedance 4/8 ohms (Config. Dependent) Sensitivity 89dB 2.83V / 1m Power reg. 25-100W/Channel Woofer (3) 3" (76mm) High Excursion Tweeter (8) 0.75" (19mm)Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB QX3CSPB PCBF **QX3CSPBF**



2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

(3) 3" (76mm) High Excursion (8) 0.75" (19mm) Aluminum James Centergy Dual Monaural Technology

The QX3CS speaker pair raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The centergy format of this bar features three individual systems to provide left and right channels in either bar and a center channel split between them. Perfect for any home entertainment system, this versatile SoundBar pair can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style guad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 70Hz, the QX3CS offers full range response with an impressive 89dB sensitivity.

The cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker pair is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers QX320 and QX330.

For outdoor/marine applications, order the QX3CSM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.



20190611

OX3LCR SoundBar 3"2-Way shallow depth in-wall LCR Soundbar







Size 7.269 h x Custom w x 3.875 d (in) 184 h x 991 w x 98 d (mm) Freq Response 70Hz-24kHz±3dB Impedance 4/8 ohms (Config. Dependent) Sensitivity 89dB 2.83V /1m Power req. 25-150W/Channel Woofer (6) 3" (76mm) High Excursion Tweeter (12) 0.75" (19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB 0X3LCRPB PCBF 0X3LCRPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

(6) 3″ (76mm) High Excursion Aluminum Driver (12) 0.75″ (19mm) Aluminum Dome Tweeters in Quad-Arrays

The QX3LCR speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The LCR format of this bar features two individual systems to provide left, right, and center channels in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high quality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 70Hz, the QX3LCR offers full range response with an impressive 89dB sensitivity.

The cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers QX320 and QX330.

For outdoor/marine applications, order the QX3LCRM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.



QX3LR SOUNDBAR /7-WAY SHALLOW DEPTH IN-WALL STERED SOUNDBAR







Size 7.269 h x Custom w x 3.875 d (in) 184.5 h x 991 w x 98 d (mm) Freq Response 70Hz-24kHz±3dB Impedance 4/8 ohms (Config. Dependent) Sensitivity 89dB 2.83V /1m Power req. 25-150W/Channel Woofer (4) 3" (76mm) High Excursion Tweeter (8) 0.75"(19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB QX3LRPB PCBF OX3LRPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

(4) 3″ (76mm) High Excursion Aluminum Driver (8) 0.75" (19mm) Aluminum Dome Tweeters in Quad-Arrays

The QX3LR speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The stereo format of this bar features two individual systems to provide both left and right channels for full stereo sound in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 70Hz, the QX3LR offers full range response with an impressive 89dB sensitivity.

The cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers QX320 and QX330.

For outdoor/marine applications, order the QX3LRM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.





QX5CS SOUNDBAR




′ 2-WAY SHALLOW DEPTH IN-WALL CENTERGY DUAL MONAURAL CENTERGY SOUNDBAR PAIR



Size Custom h x 8.125 w x 3.875 d (in) 854 h x 206 x w 98 d (mm) depth w/arille 4.125 d(in) 104(mm) Freq Response 65Hz-24kHz±3dB Impedance 4/8 ohms (Config. Dependent) Sensitivity 89dB 2.83V / 1m Power reg. 50-200W/Channel Woofer (3) 5.25" (133mm) Aluminum Tweeter (8) 0.75"(19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB OX5CSPB PCBF OX5CSPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com



The QX5CS speaker pair raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The centergy format of this bar features three individual systems to provide left and right channels in either bar and a center channel split between them. Perfect for any home entertainment system, this versatile SoundBar pair can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 65Hz, the QX5CS offers full range response with an impressive 89dB sensitivity.

The in-wall cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker pair is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers OX520 and OX530.

For outdoor/marine applications, order the QX5CSM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2'', 5/8'' etc). This is a suffix to the part number and added to the end.



QX5LCR SOUNDBAR 257 2-WAY LCB SHALLOW DEPTH IN-WALL SOUNDBAR







Frea Response

206 h x 1128 w x 98 d (mm) 65Hz-24kHz±3dB Impedance 4/8 ohms Sensitivity 89dB 2.83V /1m Power reg. 25-100W/Channel Woofer (4) 5.25" (132mm) Aluminum Tweeter (12) 0.75" (19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB OX5LCRPB PCBF QX5LCRPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

(4) 5.25" (133mm) High Excursion Aluminum Driver (12) 0.75" (19mm) Aluminum Dome Tweeters in Quad-Arrays

The QX5LCR speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The LCR format of this bar features two individual systems to provide left, right, and center channels in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 65Hz, the QX5LCR offers full range response with an impressive 89dB sensitivity.

The in-wall cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers QX520 and 0X530.

For outdoor/marine applications, order the QX5LCRM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.



QX5LR SoundBar /7-WAY SHALLOW DEPTH IN-WALL STERED SOUNDBAR







The QX5LR speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The stereo format of this bar features two individual systems to provide both left and right channels for full stereo sound in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style guad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 65Hz, the QX5LR offers full range response with an impressive 89dB sensitivity.

The in-wall cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers OX520 and OX530.

For outdoor/marine applications, order the QX5LRM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.



Freq Response Impedance

Size 8.125 h x Custom w x 3.875 d (in) 206 h x 1118 w* x 98 d (mm) 65Hz-24kHz±3dB 4/8 ohms (Config. Dependent) Sensitivity 89dB 2.83V /1m Power reg. 25-100W/Channel Woofer (4) 5.25" (132mm) Aluminum Tweeter (8) 0.75" (19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB OX5LRPB PCBF QX5LRPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

QX5LR-S SOUNDBAR 5.25″ - 2.1 FORMAT SOUNDBAR - 4″ DEPTH







Impedance* Woofer*

206 h x Custom w x 99 d (mm) Freq Response 45Hz-24kHz±3dB 4/8 ohms Sensitivity 89dB 2.83V /1m Power reg. L/R: 25-100W/Channel Sub: 50-150W/Channel 5.25" (132mm) Aluminum Tweeter* 0.75" (19mm) Aluminum Finishes White Paintable Grille (Paintable by Request Only) PCB QX5LRSPB PCBF OX5LCSPBF *Driver count and impedance are config. dependent

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

5.25" (133mm) High Excursion Aluminum Driver 0.75" (19mm) Aluminum Dome Tweeters in Quad-Arrays

The QX5LR-S speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The LR-S format of this bar features two individual systems to provide left, right, and sub channels in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high guality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 45Hz, the QX5LR-S offers full range response with an impressive 89dB sensitivity.

The in-wall cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible.

For outdoor/marine applications, order the QX5LR-SM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2'', 5/8'' etc). This is a suffix to the part number and added to the end.

