

## **Cable Line Surge & Lightning Protection**



Surge protect incoming and outgoing cable and high speed internet lines protecting them from harmful transient voltages and ground potential differences reducing lockups, glitches, reprogramming issues and lightning damage.

Improve power quality for your sophisticated electronic loads. Rebooting, reprogramming and replacing processors, circuit boards and components can be a never-ending battle. Occasional glitches in the system are as simple as equipment locking up or turning on and off without user input to wide spread damage during a severe lightning storm. Larger pulses will cause catastrophic failure while smaller pulses degrade the life and reliability of these systems and controls.

It is important to protect the incoming cable and satellite lines as well as the coaxial lines running between building. Any nearby lightning can couple onto coaxial lines and, if unprotected, ride into your home or office and destroy interconnected equipment.

## SPECIFICATIONS

Applications: CATV Cable TV & High Speed Internet

Design: Solid State

Warranty: Ten Year Unlimited Free Replacement

Operating Frequency: 5MHz to 1.2GHz

Max Data Rate: Not applicable, see operating frequency

Operating Voltage: 95V RMS/135V Peak Two Way Communication Compatible: Yes Ultra High Definition Compatible: Yes

Mode of Protection: All modes: center conductor-ground.

Response Time: < 1 nanosecond Strength: 1000 amps per wire Series Resistance: < 0.1 ohm

Insertion Loss: <0.5db (5MHz to 1.0GHz)
Dimensions (approx): 3.25"L x .5"W
Enclosure Type: Metal Weatherproof

Connection Method: F Type connection accepts RG6 or RG11

**Mounting Method:** All units come standard with an Integrated mounting bracket with ground connection.

Operating Temperature: -40° C to 85° C (-40° F to 185° F)
Weight: 0.50 lbs. to 0.75 lbs. (0.23 kg—0.34 kg) depending on

number of circuits.

Cable TV
Distributed Cable
TV
Hum Blocker
High Speed Internet



**TPD-CABLE** 


## **CABLE CONFIGURATIONS**

Model Number	Number Of Circuits	Applications	Description
TPD-CABLE	1 Circuit In/Out	Cable	F Connectors

Specifications subject to change without notice, see web site www.TPDsurge.com or latest revisions.

The highest quality cable and satellite protection available. Strategically protect coaxial cables entering the home before being distributed throughout the house. Bonding the coaxial line ground with the electrical system ground will create an equal potential ground eliminating the potential for ground loops. This will allow for the more reliable system with less chance of noise and interference contaminating video and audio signals. Use TPD-SAT2 to protect satellite radio. Unlike other technologies on the market, the TPD-CABLE performance will not degrade. You can count on the TPD-CABLE working now and 5000 surges later.

**Tech Note:** For cable or satellite extensions that enter or eave the building please refer to the TPD Phone, Cable & Data Application Design for additional information.



Transient Protection Design,
4311 William Penn Highway, Mifflintown, PA 17059
Call Technical Support at 717-436-2856 or visit us at
www.TransientProtectionDesign.com

Tech Note: For installation techniques please refer to installation manual.